



SOLD SEPARATELY
12-WCX-PWR36 – Sealed Fuse Holder

- At Battery: ¼" Ring Barrel Terminal - 18" to Fuse Holder
- Fuse 1, 10 Amp: 16 Ga. RD Power 1 - 18" to CEM16
- Fuse 2, 10 Amp: 16 Ga. RD Power 2 - 18" to CEM16
- Fuse 3, 10 Amp: 16 Ga. RD Power 3 - 18" to CEM16
- Fuse 4, 10 Amp: 16 Ga. RD Power 4 - 18" to CEM16
- 18 Ga. BK J9 5 Ground – ¼" Ring
- 18 Ga. BK J9 10 Ground – ¼" Ring

CENTER CONSOLE:

FRONT FLASH ACTIVATE

- 14 Ga. PK Flash C

HORN RING

- 16 Ga. YW/RD Horn
- 16 Ga. YW/RD Horn Ring

LIGHT & SIREN CONTROLLER:

J11 – DRY CONTACT RELAY

- Pos. 1 – 18 Ga. YW/RD Horn Trans
- Pos. 2 – 16 Ga. YW/RD Horn Ring
- Pos. 3 – 16 Ga. YW/RD Horn

J16 – SPEAKER

- Pos. 1 – 16 Ga. WH/BK Spkr Pos
- Pos. 2 – 16 Ga. WH/BK Spkr Pos 2
- Pos. 3 – 16 Ga. WH Spkr Com
- Pos. 4 – 16 Ga. WH Spkr Com 2

J6 – INPUTS

- Pos. 1 – 18 Ga. YW/RD Horn Trans
- Pos. 2 – Not Used
- Pos. 3 – Not Used
- Pos. 4 – Not Used
- Pos. 5 – Not Used
- Pos. 6 – Not Used
- Pos. 7 – Not Used
- Pos. 8 – Not Used
- Pos. 9 – Not Used
- Pos. 10 – Not Used
- Pos. 11 – Not Used
- Pos. 12 – Not Used

AUX TRIPS

- 14 Ga. TN/WH Aux Trip 1
- 14 Ga. TN/WH Aux Trip 2

FRONT FLASH ACTIVATE

- 14 Ga. PK Flash C

REAR POWER CIRCUITS